

LED Tube

Glass Body Premium

CE | IP20 | Lumens 100 l/w | CRI 70 | 270° Beam Angle | VOLTS 100-277 | PF >0.90 | -20°C to 40°C | 30,000 | 5 YEAR Warranty

- Specially designed glass housing provides excellent transparency and thermal conductivity allowing good heat dissipation.
- Opal diffuser
- Tolerance ± 7% Lumen
- Powered on one end (Standard)
- Powered on 2 ends-add letter “B”
- Add “F” for Foam packing
- Remove or bypass ballast for installation

Ordering information

Model	W	Base	Color Temperature	Input Voltage	Lumens	Diffuser	Length
AL573056	**9w**	G13	6500K	100-277V	900lm	Opal	60cm
AL573047	**9w**	G13	6500K	100-277V	900lm	Clear	60cm
AL573057	**18w**	G13	6500K	100-277V	1800lm	Opal	120cm
AL573048	**18w**	G13	6500K	100-277V	1800lm	Clear	120cm

Notes

Average life hours based on daily use of 12 hours.
The use of more than 12, to 24 hours will not harm the performance but will decrease the lifetime of the product between 25% to 35%.

Packing information

Color Sleeve packing

Model	CBM per master	Pieces per master	Box Dimensions (cm)	Gross weight (Kg)
9w	0.0176	25	65 x 16.5 x 16.5	2.85
18w	0.0340	25	125 x 16.5 x 16.5	5.5

Foam packing

Model	CBM per master	Pieces per master	Box Dimensions (cm)	Gross weight (Kg)
9w	0.0201	25	65 x 18 x 18	2.75
18w	0.0393	25	125 x 18 x 17.5	5.5