

Disk™ Series

CCT Selectable

4"/6"/8"

CERTIFIED | DOB Tech | Wet Location | LM80 | LM79 | IK 07 | 5CCT Selectable 27K-5K | 100° Beam Angle | DIM Triac | CRI 80 | UGR Up to 22 | SDCM <8 | VOLTS 120V | PF >.90 | THD 20% | -20°C~40°C | 60,000 | 5 YEAR Warranty

Americanlite® Disk™ Series incorporate DOB™ technology to create an ultra-low profile, surface-mounting LED luminaire with the performance and look of traditional downlights. Disk™ Series is designed for installation in many square, octagon and round junction boxes. Suitable for residential or commercial installations.

Americanlite® innovative selectable 5-CCT feature incorporates a switch on each fixture for simple color temperature adjustment. Not 3...but 5 different choices for every single application (2700-3000-3500-4000-5000K) and an impressive CRI 80. Too warm or too cool? Simply toggle the integrated switch to your desired setting and you are done! Whatever your application, the Disk™ luminarie is sure to give you the feel and flexibility that you need. More flexibility? Disk™ is dimmable (Triac) 10-100%.


Disk™ luminaire housing and frame are made of stamped steel; white finish standard (paintable), other colors available. Precision engineered optic provides uniform luminance from a low-profile convex lens.

Disk™ luminaire L70 at 60,000 hours projected in accordance with TM-21. EMI/RFI emissions per FCC 47CFR Part 15B. Disk™ luminaire contains no mercury or lead and RoHS compliant. Photometric testing in accordance with IES LM-79-08.

The Americanlite® Disk™Series offers unparalleled design freedom with mainstream value. Perfect for residential or commercial installations and ideal for general lighting, schools, hotels, storage areas, corridors, basements, kitchen, and many more.

Dimensions (mm)





Power	Size	A	B	C	D
10w	4"	150	22	12	97
15w	6"	186	24	12	132
20w	8"	240	34	14.2	182

Ordering information

Item	Power	Size	2700K	3000K	3500K	4000K	5000K
AL582566	10w	4"	715 lm	740 lm	753 lm	753 lm	740 lm
AL582567	15w	6"	1265 lm	1320 lm	1370 lm	1340 lm	1300 lm
AL582568	20w	8"	1700 lm	1770 lm	1815 lm	1785 lm	1760 lm

Ring	
Blank	White
SN	Satin Nickel
DB	Dark Brown
BK	Black

Compatible dimmers

Lutron	DVCL-153P-WH	CTCL-153PDH-WH	SLV-600P-WH	S-600PR-WH	DV-600P	CT-603PGH-WH	MIR-600THW-WH	MACL-153M-WH	S-600PR-WH
	DVLV-603P-IV	DVW-603PGH-WH	DVFSQ-LFH	SCL-153PR-WH	CT-600PR-WH	CT-103PR-WH	DVWCL-153PH-LA	CTCL-150H-WH	CTCL-153PR-WH
	STCL-153PH-WH	NT-1000	S-603P						
Leviton	6674	6633-P	6672	DSL06-1TW	6631	IPL06	IPV0R	1A2305	1E1205
	DB33K1	1F4205							

Notes

- Switch ON/OFF = 114,000 times
- Complies with UL 1598

- Beam Angle:
  4" = 100°
  6" = 100°
  8" = 110°

Packing information

Model	CBM (Master)	Pieces per master	Box Dimensions (CM)	Gross weight (KGS)
4"	0.0132	12	33 x 23 x 17.5	3
6"	0.0221	12	39.1 x 27.2 x 20.8	4
8"	0.0657	12	50 x 26.3 x 50	6