

Acqua XRE™

36w / 40w

IP65	IK08	LM80
Lumens 130 lxw	VOLTS 120-277	1.5Kv Surge Protection
CCT 3K-65K	120° Beam Angle	PF >.90
THD <20%	CRI >80	50,000
-30°to+50°C	3 YEAR Warranty	

The LED Acqua XRE™ Series is a modern energy efficient industrial waterproof surface mounted or suspended LED lighting fixture that features rugged and durable construction. Carries an IP65 rating that ensures integrity in damp and wet locations. Provides protection not just from ambient moisture, but also from jets of water. It is ideal for use in environments where dust, dirt, humidity or moisture are present.


The LED Acqua XRE™ Series consists of a PC housing (ABS optional) and PC diffuser (Opal). Natural silicone gel gasket bonded to the housing, captive, corrosion-resistant, without the need for clips to secure the diffuser.

Utilizes high-efficiency BMTC LED chip on metal core circuit boards. High-efficiency driver with built in 1.5kV surge suppressor operates through 277V.

Install indoors or outdoors. Use in cold or warm temperatures. Mount in high or low spaces.

The LED Acqua XRE™ Series is ideal for parking garages, exterior retail, cold storage or warehouses.

Dimensions (mm)



Ordering information

Model	Power	Size	Lumens	CCT		Housing		Options	
AL586391	36w	4'	4700	**Blank**	6500K	**Blank**	PC	**EM**	ER Driver
AL586392	40w	4'	5200	**5**	5000K	**A**	ABS		
				4	4000K				
				3	3000K				

Notes

- Lumen tolerance < 8%
- Lumens based @ 6500K
- Lumens x Watt:
  6500K = 130
  5000K = 130
  4000K = 130
  3000K = 120
- ABS Base Fixture = IK05
- Max # of fixtures allowed per line with one power input = 12
- Not intended for more than 18 hours/day
- Installation Brackets = Stainless Steel
- LED Chips - BMTC SMD 2835
- Flicker = < 30%
- EM - Emergency 2w, 3 hours

Packing information

Model	Pieces per box	Master Box (cm)	CBM (box)	Gross weight (KGS)
4'	12	120 x 31 x 22	0.0818	18