

Frameless Series

Round Recess CCT Selectable



IP20 | IK02 | CCT Selectable 3K-4K-65K 3K-4K-5K

120° Beam Angle | CRI 70 | PF >.50

VOLTS 100-277 | Lumens 80 lxw | 15,000

-20°C to 40°C | 2 YEAR Warranty


Frameless Series is an LED ultra-thin recessed downlight ideal for shallow ceiling plenum applications. Quality, housing-free recessed downlighting is achieved with its narrow body. The Frameless Series is quick and simple to install from below the ceiling with as little as 2-inch plenum clearance.

The Frameless Series offers a wide range of sizes, wattages, shapes (round and square) pairing with most of the applications, making Frameless Series a favorite among designers and architects.

Frameless Series offer a quality alternative to meet reliability and performance specifications on budget-sensitive residential or commercial projects. At the entry-level, The Frameless Series offer excellent value All-in-one unit, and is ready to install right out of box.

The Frameless Series innovative, slim design allows for easy retrofit, remodel or new construction installation from below the ceiling. The Frameless Series downlight it ideal for use in a breadth of residential, hospitality, commercial and multifamily applications.

Dimensions (mm)



Model	A	B	(cut out)
9w	85	21	55-70
18w	120	21	55-90
24w	170	21	55-135

Ordering information

Item	Power	Selectable CCT	Lumens
AL582730S	9w	3000K	720
	9w	4000K	720
	9w	6500K	720
AL582733S	18w	3000K	1440
	18w	4000K	1440
	18w	6500K	1440
AL582736S	24w	3000K	1920
	24w	4000K	1920
	24w	6500K	1920

Item	Power	Selectable CCT	Lumens
AL582780S	9w	3000K	720
	9w	4000K	720
	9w	5000K	720
AL582781S	18w	3000K	1440
	18w	4000K	1440
	18w	5000K	1440
AL582782S	24w	3000K	1920
	24w	4000K	1920
	24w	5000K	1920

Notes

- Lumen and power 10% tolerance
- 2 year warranty against defects of material and workmanship.
- 15,000 hours based on recommended use: 8 hours / day to avoid product damage or voided warranty. Indoor use only.

Packing information

Model	CBM (Master)	Pieces per master	Box Dimensions (cm)
9w Round Recessed	0.0621	100	56 x 25.5 x 43.5
18w Round Recessed	0.0548	60	49 x 40 x 28
24w Round Recessed	0.0698	40	49 x 38 x 37.5