



# MWC™

## 15w/20w/30w
## Single CCT
## CCT & Power Selectable

LISTED

Wet Location | IP65 | IK08

LM79 | LM80 | Lumens up to 135 LxW

Photocell | 100° Beam Angle | VOLTS 120-277

Power Selectable | CCT Selectable 3K-4K-5K | CCT 5000K

2.5kV Surge Protection | DIM 0-10V | CRI >80

PF >.90 | THD 20% | 100,000

-20°C-45°C | 5 YEAR Warranty


The MWC™ LED Wall Pack Series incorporates advanced LED technology and optical design to bring you a slim-profile luminaire with uncompromising performance.

The MWC™ LED wall mount luminaire combines optical performance, energy efficiency and long-term reliability in an advanced, low-profile design. Utilizing the latest LED technology, with CCT & Power Selectable, the MWC luminaire delivers unparalleled uniformity resulting in greater installation spacing. This fixture provides area coverage equivalence up to 100W Metal Halide while achieving substantial energy and maintenance savings.

The MWC™ Luminaire PC front cover is impact-resistant polycarbonate which is fully gasketed. All electronics are protected in the upper housing. Housing is sealed against moisture and environmental contaminants. Lumileds 2835 LEDs, UL 0-10v Dimming Driver with 2.5 KV Surge protection and integral photocell (Turn-on<30Lux /Turn-off>100Lux) operate at 120v-277v and are fully enclosed in the upper housing. There are no user serviceable parts. Back housing easily mounts to any recessed junction box. With all electronics in upper housing the open lower section makes wiring easy

The Innovative MWC™ wall mount luminaire delivers a broad selection of solutions with superior illumination, reliability, ease of installation, controllability, and application versatility, and multiple control solutions all in a sleek, architectural style. For outdoor applications such as building entrances & perimeter lighting, side and rear exit doors, stairways and entry path, loading docks, schools,apartment buildings, retail & commercial buildings.

## Dimensions (mm)




## Ordering information

**Single CCT**

| Model | Power | Lumens | CCT | |
|---|---|---|---|---|
| AL674377 | 15w | 2025lm | Blank | 5000K |
| AL674378 | 20w | 2700lm | 57 | 5700K |
| AL674379 | 30w | 4050lm | 4 | 4000K |

**CCT Select / Power Select**

| Model | Power Select | CCT Select | Lumens |
|---|---|---|---|
| AL674380 | 15w/10w/8w | 3K/4K/5K | 2025/1350/1080 |
| AL674381 | 20w/15w/10w | 3K/4K/5K | 2700/2025/1350 |
| AL674382 | 30w/25w/15w | 3K/4K/5K | 3750/3375/2025 |

## Notes

- DLC Premium 5.1
- 30w Selectable=NO DLC
- Driver Brand = HBE
- Lumens: 5K/57K= 135lxw
  4K=130lxw 3K=125lxw
- Lumen Tolerance up to 10%
- Power Select Models, lumens based on 5K
- L/N-PE: 2.5kV, L-N: 2.5kV
- LED = Lumileds 2835
- 100,000 hours life @ <Tc 65°C

## Packing information

| Model | Pieces per master | Box Dimensions (cm) | CBM (Master) | Gross Weight (KG) |
|---|---|---|---|---|
| 15w 20w 30w | 10 | 41.7 x 28.5 x 23.9 | 0.0284 | 9 |